



SK1207 ESD Packing Tape

Specification:

Model:SK1207

Material:OPP film

Length:36meters

Width:(12,20,25,30,40,50,100)mm

Thickness:0.06mm

Color:Transparent

Friction band voltage <50V

Static discharge time < 0.5s

Jumbo Roll:1000mm*36m

High temperature resistance:Normal

OPP ESD Packing Tapes were developed to protect static sensitive products from static electricity generated by triboelectricity when they are unrolled or removed from various objects our ESD packing tapes relatively generate very low static voltage while normal tapes generate about over 1KV to 9.5KV to 14KV under the same conditions.

Application:

*Bundle of DIP IC Tube

*Seal Static Shielding Bag

*Pack Conductive IC Tray

*Pack Wafer Carrier

*Attach a Note in Clean-room

*EMI Shielding

*Holes or Connector Pins

*Covers for External Plugs

Features of OPP ESD Packing Tape:

*Keep permanent anti-static properties

*Strong adhesive power

*Environment friendly material



Warning: LPD Trade products are made of conductive material. To avoid the risk of electric shock, do not use item close to live currency/wire.

LPD Trade Inc

Address: 145 Inland Dr NE,
Atlanta, GA 30342 USA

E-mail: doron@lpdtrade.com

Phone #: 404-255-9767

Website: www.lpdtrade.com